

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
4 March 2004 (04.03.2004)


PCT

(10) International Publication Number  
WO 2004/018911 A1

- (51) International Patent Classification<sup>7</sup>: F16K 1/22 (DE). PETRI, Bernhard [DE/DE]; Glacisweg 17, 55252 Mainz-Kastel (DE).
- (21) International Application Number: PCT/EP2002/009144 (74) Agent: PREISSNER, Nicolaus; Flügel Preissner Kastel, Haimhauserstrasse 1, 80802 München (DE).
- (22) International Filing Date: 14 August 2002 (14.08.2002) (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (*for all designated States except US*): NORD-MICRO AG & CO. OHG [DE/DE]; Victor-Slotosch-Strasse 20, 60388 Frankfurt/Main (DE).
- (72) Inventors; and (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, (75) Inventors/Applicants (*for US only*): DREISILKER, Ralf [DE/DE]; Werner-Buschmann-Str. 62, 42553 Velbert

[Continued on next page]

(54) Title: BUTTERFLY VALVE FOR CONTROLLING A GAS PRESSURE



(57) Abstract: A butterfly valve for controlling a gas pressure, in particular inside a cabin of an aircraft, comprises a valve housing (10) having a longitudinal axis (11), a shaft (20) having a rotation axis (21), and a closure member (30) connected to the shaft (20). The closure member (30) is pivotally mounted in the valve housing (10) for rotation about the rotation axis (21) between an open position and a closed position. Moreover, the closure member (30) consists of a first disk (40) and a complementary second disk (50) which abut against each other. The first disk (40) and the second disk (50) are symmetrically arranged with regard to a symmetric axis (31) extending at a predetermined angle of inclination to the rotation axis (21). Such a butterfly valve ensures a restricted cross-sectional area of the valve housing (10), even if breaking of the closure member (30) occurs.

WO 2004/018911 A1



ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK,  
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*